NSN 5962-01-376-1630

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-376-1630

Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
280.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Input Circuit Pattern:
8 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
3.50 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Dual operational amplifier, bi-fet
Voltage Rating And Type Per Characteristic:
-18.0 volts power source and 18.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-376-1630

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0