Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-376-3235

Body Length:

0.800 inches

Body Width:

0.400 inches

Body Height:

0.240 inches

Operating Tempurature Range:

-30.0/+85.0 degrees celsius

Storage Tempurature Range:

-55.0/+125.0 degrees celsius

End Application:

5895-01-299-3417 converter, signal data

Features Provided:

Monolithic and w/buffered output

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

1 input

Design Function And Quantity:

1 generator, pulse

Current Rating Per Characteristic:

50.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 0.0 volts power source

Hybrid Technology Type:

Monolithic

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-376-3235

Hybrid Microcircuit - Page 2 of 2

Fiig: A458a0

