NSN 5962-01-376-3236

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-376-3236 **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Body Height:** 0.240 inches **Operating Tempurature Range:** -30.0/+85.0 degrees celsius **Storage Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** 5895-01-299-3417 converter, signal data **Features Provided:** Monolithic and w/buffered output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 1 input **Design Function And Quantity:** 1 generator, pulse **Current Rating Per Characteristic:** 50.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -8.0 volts power source and 0.0 volts power source **Hybrid Technology Type:** Monolithic **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-376-3236

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0