

View Online at <https://aerobasegroup.com/nsn/5962-01-376-4561>

**Body Length:**

0.390 inches

**Body Width:**

Between 0.235 inches and 0.260 inches

**Body Height:**

Between 0.045 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

300.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

High speed and monolithic and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

4 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

2 comparator, voltage, differential

**Case Outline Source And Designator:**

F-2 mil-m-38510

**Current Rating Per Characteristic:**

30.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-7.0 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, high to low level output and 25.00 nanoseconds propagation delay time, low to high level output

**Special Features:**

Critical item for specifications, tolerance, and application

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0