Memory Microcircuit - Page 1 of 1





# **Operating Tempurature Range:**

-10.0/+80.0 degrees celsius

Storage Tempurature Range:

-65.0/+125.0 degrees celsius

## **End Application:**

Enditem e/i fscm 03950

### **Features Provided:**

Programmed and tested to mil-std-883

### Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

N-type metal oxide-semiconductor logic

#### **Product Name:**

Microcircuit digital 131072-bit read only memor (16384x8)

### Voltage Rating And Type Per Characteristic:

-0.6 volts absolute input and 6.0 volts absolute input and -0.6 volts absolute output and 6.0 volts absolute output

#### Time Rating Per Chacteristic:

250.00 nanoseconds access

### Memory Device Type:

Eprom

### Hybrid Technology Type:

Monolithic

#### Test Data Document:

05869-726038-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

28 printed circuit

### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0