

View Online at <https://aerobasegroup.com/nsn/5962-01-377-0855>

**Body Length:**

1.280 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

0.185 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

High impedance and asynchronous and w/clock and w/reset and bidirectional and bipolar and programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

22 input

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Current Rating Per Characteristic:**

200.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

Registered and-or logic array - invalid i/o access detector

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, high to low level output and 20.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0