NSN 5962-01-377-2402

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-377-2402

| view Offinie at https://defobasegroup.com/nsi//3302-01-377-2402 |
|--|
| Body Length: |
| Between 1.140 inches and 1.180 inches |
| Body Width: |
| Between 1.140 inches and 1.180 inches |
| Body Height: |
| Between 0.070 inches and 0.145 inches |
| Maximum Power Dissipation Rating: |
| 1.5 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and w/reset and w/resistor and w/clock |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Pin grid array |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Design Function And Quantity: |
| 1 control |
| Case Outline Source And Designator: |
| P-ac mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| 16mhz microcontroller with 16 bytes of on-chip eprom |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Capitance Rating Per Characteristic: |
| 3.00 input picofarads |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 68 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

Yes - demil/mli

NSN 5962-01-377-2402

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0