

View Online at <https://aerobasegroup.com/nsn/5962-01-377-4987>

Body Length:

0.440 inches

Body Width:

Between 0.245 inches and 0.285 inches

Body Height:

0.100 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Burn in and electrostatic sensitive and hermetically sealed and monolithic and tested to mil-std-883 and w/buffered output

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

8 channel and 5 input

Design Function And Quantity:

1 selector, data, eight to one line

Case Outline Source And Designator:

F-5 mil-m-38510

Terminal Surface Treatment:

Nickel and solder

Product Name:

8-channel buffered data selector

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 20.5 volts input

Capitance Rating Per Characteristic:

15.00 input picofarads

Time Rating Per Characteristic:

500.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0