NSN 5962-01-377-5739

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-377-5739

Body Length: 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Static operation and electrostatic sensitive and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Case Outline Source And Designator:** F-5 mil-m-38510 **Current Rating Per Characteristic:** 70.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 4.00 input picofarads and 7.00 output picofarads **Time Rating Per Chacteristic:** 25.00 nanoseconds access Memory Device Type: Ram **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a Unit Of Measure:

NSN 5962-01-377-5739

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

