NSN 5962-01-378-3129

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-378-3129

view Offiline at https://derobasegroup.com/histi/0302-01-370-3123
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in, mil-std-883, class b and compatible cmos and compatible dtl and electrostatic sensitive and tested to mil-std-883 and w/ope
collector and monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
3 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 converter, voltage to frequency and 1 converter, frequency to voltage
Case Outline Source And Designator:
A-2 mil-m-38510
Current Rating Per Characteristic:
20.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Product Name:
Converter, voltage/frequency
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Special Features:
Esd; operating frequency is 100k hz; supply voltage is +/- 18v dc
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5962-01-378-3129

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0