

View Online at <https://aerobasegroup.com/nsn/5962-01-378-4313>

**Body Length:**

Between 1.080 inches and 1.135 inches

**Body Width:**

Between 1.080 inches and 1.135 inches

**Body Height:**

Between 0.070 inches and 0.145 inches

**Maximum Power Dissipation Rating:**

1.5 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Programmed and ultraviolet erasable and w/clock and w/enable and w/disable and asynchronous and bidirectional

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Pin grid array

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

64 input

**Case Outline Source And Designator:**

P-bc mil-m-38510

**Current Rating Per Characteristic:**

300.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

1800 gate epld

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

20.00 input picofarads and 20.00 output picofarads

**Time Rating Per Characteristic:**

75.00 nanoseconds access

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

68 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0