

View Online at <https://aerobasegroup.com/nsn/5962-01-379-0094>

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

6625-01-323-3125 test set, computer

**Features Provided:**

W/enable and 3-state output and w/open collector and bidirectional and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

24 input

**Design Function And Quantity:**

1 transceiver

**Current Rating Per Characteristic:**

175.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

Transceiver, general purpose interface bus

**Voltage Rating And Type Per Characteristic:**

-1.0 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

80.00 input picofarads and 80.00 output picofarads

**Time Rating Per Characteristic:**

30.00 nanoseconds propagation delay

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0