

View Online at <https://aerobasegroup.com/nsn/5962-01-379-0094>

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-323-3125 test set, computer

Features Provided:

W/enable and 3-state output and w/open collector and bidirectional and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

24 input

Design Function And Quantity:

1 transceiver

Current Rating Per Characteristic:

175.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Transceiver, general purpose interface bus

Voltage Rating And Type Per Characteristic:

-1.0 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

80.00 input picofarads and 80.00 output picofarads

Time Rating Per Characteristic:

30.00 nanoseconds propagation delay

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0