

View Online at <https://aerobasegroup.com/nsn/5962-01-379-4679>

Maximum Power Dissipation Rating:

0.6 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Wgu-2c/b guid e/i fscm 96214

Features Provided:

Bipolar and programmed and tested to mil-std-883

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

D-8 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Programmable array logic, altered

Voltage Rating And Type Per Characteristic:

-0.5 volts absolute input and 5.5 volts absolute input

Memory Device Type:

Pal

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil--38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

81349--38510/50605bra government specification and 67268-5962-8515505ra government standard

Departure From Cited Designator:

Programmed per: 704as11591-102

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0