

View Online at <https://aerobasegroup.com/nsn/5962-01-379-4679>

**Maximum Power Dissipation Rating:**

0.6 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Wgu-2c/b guid e/i fscm 96214

**Features Provided:**

Bipolar and programmed and tested to mil-std-883

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

16 input

**Case Outline Source And Designator:**

D-8 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Programmable array logic, altered

**Voltage Rating And Type Per Characteristic:**

-0.5 volts absolute input and 5.5 volts absolute input

**Memory Device Type:**

Pal

**Hybrid Technology Type:**

Monolithic

**Test Data Document:**

81349-mil--38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Specification Data:**

81349--38510/50605bra government specification and 67268-5962-8515505ra government standard

**Departure From Cited Designator:**

Programmed per: 704as11591-102

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0