NSN 5962-01-380-1527



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-380-1527 **Body Length:** Between 0.342 inches and 0.358 inches **Body Width:** Between 0.342 inches and 0.358 inches **Body Height:** Between 0.050 inches and 0.088 inches **Maximum Power Dissipation Rating:** 198.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and burn in and monolithic and schottky and tested to mil-std-883 **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Design Function And Quantity:** 1 driver **Case Outline Source And Designator:** C-2 mil-m-38510 **Current Rating Per Characteristic:** 50.00 milliamperes collector cutoff current, dc, base open not applicable and 200.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Product Name:** Hex 2-input or drivers **Voltage Rating And Type Per Characteristic:** -1.2 volts input and 7.0 volts input **Time Rating Per Chacteristic:** 1.00 nanoseconds propagation delay time, low to high level output and 7.50 nanoseconds propagation delay time, low to high level output **Terminal Type And Quantity:**

20 leadless

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-380-1527

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0