

View Online at <https://aerobasegroup.com/nsn/5962-01-380-2263>

Body Length:

0.370 inches

Body Width:

0.370 inches

Body Height:

0.085 inches

Maximum Power Dissipation Rating:

536.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and electrostatic sensitive

Inclosure Material:

Glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

5 receiver, line differential

Current Rating Per Characteristic:

70.00 microamperes reverse current, dc microamperes

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.62 volts low level output

Time Rating Per Characteristic:

2.70 nanoseconds propagation delay time, high to low level output and 2.70 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0