NSN 5962-01-380-6677

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-380-6677

| Maximum Power Dissipation Rating: |
|---|
| 250.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Pacer dawn |
| Features Provided: |
| Monolithic and electrostatic sensitive and tested to mil-std-883 |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leaded chip carrier |
| Output Logic Form: |
| Complementary-oxidized-silicon logic |
| Criticality Code Justification: |
| Feat |
| Design Function And Quantity: |
| 32 driver |
| Product Name: |
| Microcircuit, digital, cmos serial input lcd driver, monolithic silicon |
| Voltage Rating And Type Per Characteristic: |
| -3.0 volts input and 10.0 volts input |
| Special Features: |
| Esd |
| Terminal Type And Quantity: |
| 40 leadless |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A458a0 |
| |