NSN 5962-01-381-0155

Memory Microcircuit - Page 1 of 2

24 printed circuit



View Online at https://aerobasegroup.com/nsn/5962-01-381-0155

Body Length:
1.280 inches
Body Width:
0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
1.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and electrostatic sensitive and programmed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
22 input
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
15.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Logic array, semicustom, (22v10), prgmd
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Capitance Rating Per Characteristic:
8.00 input picofarads and 12.00 output picofarads
Time Rating Per Chacteristic:
40.00 nanoseconds delay
Memory Device Type:
Pai
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

NSN 5962-01-381-0155

Memory Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

