

View Online at <https://aerobasegroup.com/nsn/5962-01-381-2970>

**Body Length:**

1.280 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Pacer dawn

**Features Provided:**

Bipolar and burn in, mil-std-883, class b and electrostatic sensitive and programmable and tested to mil-std-883

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

22 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Product Name:**

Microcircuits, cpu card address decode and control pal

**Voltage Rating And Type Per Characteristic:**

0.5 volts total supply and 7.0 volts total supply

**Memory Device Type:**

Pal

**Special Features:**

Esd, altered item using 5962-86053011x, cage 67268

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0