## NSN 5962-01-381-3234

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-381-3234

## **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.2 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Pacer dawn **Features Provided:** Bipolar and burn in, mil-std-883, class b and electrostatic sensitive and programmable and tested to mil-std-883 **Inclosure Material:** Ceramic Inclosure Configuration: Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 22 input **Criticality Code Justification:** Feat **Case Outline Source And Designator:** D-9 mil-m-38510 **Product Name:** Microcircuits, 1553 card, ram arbitration control pal Voltage Rating And Type Per Characteristic: 0.5 volts total supply and 7.0 volts total supply Memory Device Type: Pal **Special Features:** Esd, altered item using 5962-8605301lx, cage 67268 **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

## NSN 5962-01-381-3234

Memory Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A458a0

