NSN 5962-01-381-4824

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-381-4824

view Offline at https://defobasegroup.com/nsn/3302-01-301-4024
Body Length:
Between 1.540 inches and 1.595 inches
Body Width:
Between 1.540 inches and 1.595 inches
Body Height:
Between 0.100 inches and 0.140 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Aim-120
Features Provided:
Burn in, mil-std-883, class b and electrostatic sensitive and tested to mil-std-883
Inclosure Material:
Ceramic
Inclosure Configuration:
Pin grid array
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Criticality Code Justification:
Feat
Design Function And Quantity:
6072 gate, array
Current Rating Per Characteristic:
10.00 milliamperes reverse current, dc microamperes
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit digital 6072 gate array, cmos lsi rc correlator timing
Voltage Rating And Type Per Characteristic:
-0.3 volts total supply and 7.0 volts total supply and -0.3 volts input and 0.3 volts input
Special Features:
Esd; input current is porm 10ma
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
180 pin
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-381-4824

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0