NSN 5962-01-381-7498

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-381-7498

| Body Length:0.890 inchesBody Width:0.310 inchesBody Height:0.205 inchesMaximum Power Dissipation Rating:450.0 milliwattsOperating Tempurature Range:-40.0/+85.0 degrees celsiusStorage Tempurature Range:-65.0/+125.0 degrees celsiusEnd Application: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Body Width:0.310 inchesBody Height:0.205 inchesMaximum Power Dissipation Rating:450.0 milliwattsOperating Tempurature Range:-40.0/+85.0 degrees celsiusStorage Tempurature Range:-65.0/+125.0 degrees celsiusEnd Application: |
| 0.310 inches Body Height: 0.205 inches Maximum Power Dissipation Rating: 450.0 milliwatts Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| Body Height:0.205 inchesMaximum Power Dissipation Rating:450.0 milliwattsOperating Tempurature Range:-40.0/+85.0 degrees celsiusStorage Tempurature Range:-65.0/+125.0 degrees celsiusEnd Application: |
| 0.205 inches Maximum Power Dissipation Rating: 450.0 milliwatts Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| Maximum Power Dissipation Rating: 450.0 milliwatts Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| 450.0 milliwatts Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| Storage Tempurature Range: -65.0/+125.0 degrees celsius End Application: |
| -65.0/+125.0 degrees celsius End Application: |
| End Application: |
| |
| |
| 6625-01-292-7347 calibrator voltage |
| Features Provided: |
| Monolithic and positive outputs and electrostatic sensitive |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Design Function And Quantity: |
| 4 switch, bilateral |
| Current Rating Per Characteristic: |
| 30.00 milliamperes reverse current, dc microamperes |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 44.0 volts power source |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |