Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-381-7508

# Maximum Power Dissipation Rating: 1.0 watts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application:

Next assembly: a06g2795 used on: a05g0516-3

## **Features Provided:**

Programmed and ultraviolet erasable

Inclosure Configuration:

Dual-in-line

Case Outline Source And Designator:

D-10 mil-m-38510

**Terminal Surface Treatment:** 

Solder

## Voltage Rating And Type Per Characteristic:

-0.6 volts applied and 6.25 volts applied

## **Time Rating Per Chacteristic:**

200.00 nanoseconds access

## Memory Device Type:

Eprom

Hybrid Technology Type:

Monolithic

## **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0