NSN 5962-01-381-7672

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-381-7672

Body Length:
1.450 inches
Body Width:
1.120 inches
Body Height:
0.330 inches
Maximum Power Dissipation Rating:
6.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hybrid
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Design Function And Quantity:
1 converter, dc
Current Rating Per Characteristic:
40.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Linear dc/dc converter, hybrid
Voltage Rating And Type Per Characteristic:
-0.5 volts absolute input and 50.0 volts absolute input and 5.0 volts output
Hybrid Technology Type:
Monolithic
Special Features:
Single channel
Test Data Document:
81349-mil-h-38534 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883
standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-1835 standard (includes
industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-480 standard (includes industry or
association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin

01 type and bigless and vices and a finish

Specification Data:

67268-5962-92139 government standard

Specification Or Standard:

NSN 5962-01-381-7672

Hybrid Microcircuit - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0