## NSN 5962-01-381-7985

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-381-7985

**Body Length:** 

Between 1.080 inches and 1.135 inches

**Body Width:** 

Between 1.080 inches and 1.135 inches

**Body Height:** 

0.345 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Electrostatic sensitive and programmable and bidirectional and w/clock and w/reset and high impedance and 3-state output

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Pin grid array

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

37 input and 40 input

**Case Outline Source And Designator:** 

P-bc mil-m-38510

**Current Rating Per Characteristic:** 

250.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Gold

**Product Name:** 

12 x 12 4200 gate programmable array

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 output picofarads

**Memory Device Type:** 

Pal

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

84 pin

## NSN 5962-01-381-7985

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0