

View Online at <https://aerobasegroup.com/nsn/5962-01-381-8592>

**Maximum Power Dissipation Rating:**

192.50 milliwatts

**Operating Temperature Range:**

-55.5/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bipolar and low power and schottky and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

4 receiver, line differential

**Case Outline Source And Designator:**

D-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Quadruple differential line receiver

**Voltage Rating And Type Per Characteristic:**

4.5 volts applied and 5.5 volts applied

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Specification Data:**

67268-5962-90766 government standard

**Specification Or Standard:**

01 type and e case and a finish

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0