

View Online at <https://aerobasegroup.com/nsn/5962-01-382-0172>

Body Length:

1.490 inches

Body Width:

0.610 inches

Body Height:

0.217 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

B-2 anitiskid control uni (acu)

Features Provided:

Burn in, mil-std-883, class b and electrostatic sensitive and monolithic and programmable and ultraviolet erasable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Criticality Code Justification:

Feat

Case Outline Source And Designator:

D-10 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital 65, 536, uv erasable prom monolithic silicon

Voltage Rating And Type Per Characteristic:

4.5 volts total supply and 5.5 volts total supply

Memory Device Type:

Rom

Special Features:

Esd, high bite, item altered from smd 8200505ya. Used on 6005351-4, wheel board printed wiring board

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

21 printed circuit

Specification Data:

67268-8200505yx government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0