

View Online at <https://aerobasegroup.com/nsn/5962-01-382-0172>

**Body Length:**

1.490 inches

**Body Width:**

0.610 inches

**Body Height:**

0.217 inches

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

B-2 anitiskid control uni (acu)

**Features Provided:**

Burn in, mil-std-883, class b and electrostatic sensitive and monolithic and programmable and ultraviolet erasable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

N-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

16 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-10 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital 65, 536, uv erasable prom monolithic silicon

**Voltage Rating And Type Per Characteristic:**

4.5 volts total supply and 5.5 volts total supply

**Memory Device Type:**

Rom

**Special Features:**

Esd, high bite, item altered from smd 8200505ya. Used on 6005351-4, wheel board printed wiring board

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

21 printed circuit

**Specification Data:**

67268-8200505yx government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0