NSN 5962-01-382-4247

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-382-4247

View Online at https://aerobasegroup.com/nsn/5962-01-382-4247
Body Length:
0.640 inches
Body Width:
Between 0.300 inches and 0.420 inches
Body Height:
Between 0.045 inches and 0.090 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Ultraviolet erasable and w/inhibit and w/disable
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
14 input
Case Outline Source And Designator:
F-6 mil-m-38510
Current Rating Per Characteristic:
120.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
6.00 input picofarads and 12.00 output picofarads
Time Rating Per Chacteristic:
45.00 nanoseconds access
Memory Device Type:
Eprom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 flat leads
Shelf Life:

N/a

NSN 5962-01-382-4247

Memory Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0