NSN 5962-01-382-4806

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-382-4806 **Body Length:** 0.785 inches **Body Width:** 0.310 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nor **Current Rating Per Characteristic:** 100.00 milliamperes forward current, nonrepetitive, peak total value **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts absolute input and 6.0 volts absolute input **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 pin **Specification Data:** 81349-mil-m-38510/750 government specification Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5962-01-382-4806

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0