

View Online at <https://aerobasegroup.com/nsn/5962-01-382-6143>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Used on: 8506200-911

Features Provided:

Programmed and tested to mil-std-883

Inclosure Configuration:

Leadless flat pack

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

C-2 mil-m-38510

Product Name:

16-input 4-output registered and-or gate array

Voltage Rating And Type Per Characteristic:

4.5 volts applied and 5.5 volts applied

Memory Device Type:

Pal

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

67268-81036102a government standard

Departure From Cited Designator:

Programmed per: (07187)tt8514392-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0