

View Online at <https://aerobasegroup.com/nsn/5962-01-382-8117>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Features Provided:

Programmed and electrostatic sensitive

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Case Outline Source And Designator:

C-4 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

4.5 volts applied and 5.5 volts applied

Memory Device Type:

Prom

Hybrid Technology Type:

Monolithic

Special Features:

One time programmable

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Specification Data:

67268-5962-88734033a government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0