

View Online at <https://aerobasegroup.com/nsn/5962-01-383-2881>

**Body Length:**

Between 1.270 inches and 1.290 inches

**Body Width:**

Between 0.590 inches and 0.610 inches

**Body Height:**

Between 0.205 inches and 0.225 inches

**Maximum Power Dissipation Rating:**

1.04 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Lgm-030f/g, 118a

**Features Provided:**

Bipolar and burn in, mil-std-883, class b and electrostatic sensitive and monolithic and programmed and tested to mil-std-883

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

14 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-3 mil-m-38510

**Current Rating Per Characteristic:**

190.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

Programmable read only memory (prom) anti-intrusion alarm set operational software

**Voltage Rating And Type Per Characteristic:**

-0.3 volts power source and 7.0 volts power source and 5.5 volts input

**Capitance Rating Per Characteristic:**

10.00 input picofarads

**Time Rating Per Characteristic:**

100.00 nanoseconds propagation delay and 100.00 nanoseconds access

**Memory Device Type:**

Prom

**Special Features:**

Esd; altered item programmed using 14933/82009a1jx (which is substitute for 82009i1jx) using d180-18228-1

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0