NSN 5962-01-384-1976

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-384-1976 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.198 inches **Maximum Power Dissipation Rating:** 104.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Design Function And Quantity:** 2 flip-flop, j-k **Current Rating Per Characteristic:** 30.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes and 5.00 milliamperes reverse current, dc microamperes **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 0.5 volts input and 7.0 volts input **Time Rating Per Chacteristic:** 5.00 nanoseconds recovery **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit **Specification Data:** 81349-mil-m-38510j government specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0