

View Online at <https://aerobasegroup.com/nsn/5962-01-384-6914>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Fleet data re e/i fscm 05869

Features Provided:

Bipolar and programmed and tested to mil-std-883

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

D-8 mil-m-38510

Product Name:

Programmed array logic mk-48 adcap reproduce unit data buffer control pal-u20

Voltage Rating And Type Per Characteristic:

-1.5 volts absolute input and 5.5 volts absolute input

Memory Device Type:

Pal

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

67268-85065 government standard

Specification Or Standard:

02 type and r case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0