

View Online at <https://aerobasegroup.com/nsn/5962-01-386-3131>

Maximum Power Dissipation Rating:

1.04 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Landing gear e/i fscm 80477

Features Provided:

Bipolar and electrostatic sensitive and programmed

Inclosure Configuration:

Dual-in-line

Case Outline Source And Designator:

D-3 mil-m-38510

Product Name:

8k x 8 bipolar prom

Voltage Rating And Type Per Characteristic:

-0.3 volts absolute input and 7.0 volts absolute input

Time Rating Per Characteristic:

100.00 nanoseconds af output megawatts

Memory Device Type:

Prom

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0