

View Online at <https://aerobasegroup.com/nsn/5962-01-386-3605>

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Hsvd ac-130u e/i fscm 43999

Features Provided:

Electrostatic sensitive and programmed and ultraviolet erasable

Inclosure Configuration:

Dual-in-line

Case Outline Source And Designator:

D-10 mil-m-38510

Voltage Rating And Type Per Characteristic:

4.5 volts applied and 5.5 volts applied

Time Rating Per Characteristic:

200.00 nanoseconds access

Memory Device Type:

Eprom

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Departure From Cited Designator:

Programmed per: es 1671

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0