

View Online at <https://aerobasegroup.com/nsn/5962-01-388-0029>

Maximum Power Dissipation Rating:

1.2 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Used on: cobra dane next assembly: g526534

Features Provided:

Electrostatic sensitive and programmed and tested to mil-std-883

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Case Outline Source And Designator:

D-9 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

22-input 10-output and-or0logic array

Voltage Rating And Type Per Characteristic:

-0.5 volts applied and 7.0 volts applied

Time Rating Per Characteristic:

25.00 nanoseconds access

Memory Device Type:

Pal

Hybrid Technology Type:

Monolithic

Special Features:

One-time programmable

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

24 printed circuit

Specification Data:

67267-5962-8867001la government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0