

View Online at <https://aerobasegroup.com/nsn/5962-01-388-0098>

Maximum Power Dissipation Rating:

739.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Next assembly: g526515 used on: cobra dane

Features Provided:

Bipolar and burn in and programmed and schottky and electrostatic sensitive and tested to mil-std-883 and 3-state output

Inclosure Configuration:

Dual-in-line

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

256-bit fused prom

Voltage Rating And Type Per Characteristic:

-0.5 volts applied and 7.0 volts applied

Memory Device Type:

Prom

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 printed circuit

Specification Data:

81349--38510/20702bea government specification

Departure From Cited Designator:

Programmed per: prg553942-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0