## NSN 5962-01-391-0274

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-391-0274

| Operating Tempurature Range:   |
|--|
| -55.0/+125.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and burn in and programmable   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Case Outline Source And Designator:  |
| D-9 mil-m-38510  |
| Terminal Surface Treatment:  |
| Solder   |
| Product Name:  |
| Pal22v10-30  |
| Voltage Rating And Type Per Characteristic:  |
| 7.0 volts power source   |
| Time Rating Per Chacteristic:  |
| 30.00 nanoseconds access   |
| Memory Device Type:  |
| Pal  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 24 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |