NSN 5962-01-391-1678

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-391-1678

| Maximum Power Dissipation Rating: |
|---|
| 1.5 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and burn in and electrostatic sensitive and programmable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Case Outline Source And Designator: |
| D-9 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Programmable pal 20v8 |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 20.00 nanoseconds access |
| Memory Device Type: |
| Pal |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |