## NSN 5962-01-391-2512

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-391-2512

Maximum Power Dissipation Rating:  1.0 watts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application:  Cv-3993/sys-2 e/i fscm 21877  Features Provided: Programmed and erasable and synchronous Inclosure Configuration:  Dual-in-line  Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal  Hybrid Technology Type: Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a  Unit Of Measure: Demilitarization: Yes - demil/mli	
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Cv-3993/sys-2 e/i fscm 21877 Features Provided: Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal Hybrid Technology Type: Monolithic Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application: Cv-3993/sys-2 e/i fscm 21877  Features Provided: Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line  Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input  Memory Device Type: Pal  Hybrid Technology Type: Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a  Unit Of Measure: Demilitarization:	1.0 watts
Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: Cv-3993/sys-2 e/i fscm 21877 Features Provided: Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal Hybrid Technology Type: Monolithic Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	Operating Tempurature Range:
-65.0/+150.0 degrees celsius  End Application:  Cv-3993/sys-2 e/i fscm 21877  Features Provided:  Programmed and erasable and synchronous Inclosure Configuration:  Dual-in-line  Voltage Rating And Type Per Characteristic:  -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type:  Pal  Hybrid Technology Type:  Monolithic  Terminal Type And Quantity:  28 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	-55.0/+125.0 degrees celsius
End Application:  Cv-3993/sys-2 e/i fscm 21877  Features Provided:  Programmed and erasable and synchronous  Inclosure Configuration:  Dual-in-line  Voltage Rating And Type Per Characteristic:  -3.0 volts absolute input and 7.0 volts absolute input  Memory Device Type:  Pal  Hybrid Technology Type:  Monolithic  Terminal Type And Quantity:  28 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Storage Tempurature Range:
Cv-3993/sys-2 e/i fscm 21877  Features Provided: Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line  Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal  Hybrid Technology Type: Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:	-65.0/+150.0 degrees celsius
Features Provided: Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal Hybrid Technology Type: Monolithic Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	End Application:
Programmed and erasable and synchronous Inclosure Configuration: Dual-in-line Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal Hybrid Technology Type: Monolithic Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	Cv-3993/sys-2 e/i fscm 21877
Inclosure Configuration:  Dual-in-line  Voltage Rating And Type Per Characteristic:  -3.0 volts absolute input and 7.0 volts absolute input  Memory Device Type:  Pal  Hybrid Technology Type:  Monolithic  Terminal Type And Quantity:  28 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Features Provided:
Dual-in-line  Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input  Memory Device Type: Pal  Hybrid Technology Type: Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Programmed and erasable and synchronous
Voltage Rating And Type Per Characteristic: -3.0 volts absolute input and 7.0 volts absolute input Memory Device Type: Pal Hybrid Technology Type: Monolithic Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Configuration:
-3.0 volts absolute input and 7.0 volts absolute input  Memory Device Type: Pal  Hybrid Technology Type: Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:	Dual-in-line
Memory Device Type:  Pal  Hybrid Technology Type:  Monolithic  Terminal Type And Quantity:  28 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Voltage Rating And Type Per Characteristic:
Pal  Hybrid Technology Type:  Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:	-3.0 volts absolute input and 7.0 volts absolute input
Hybrid Technology Type:  Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Memory Device Type:
Monolithic  Terminal Type And Quantity: 28 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:	Pal
Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization:	Hybrid Technology Type:
28 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization:	Monolithic
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	28 printed circuit
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
Yes - demil/mli	Demilitarization:
	Yes - demil/mli
Fiig:	Fiig:
A458a0	A458a0