NSN 5962-01-391-9714

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-391-9714

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.140 inches
Maximum Power Dissipation Rating:
900.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
4 input
Design Function And Quantity:
4 switch, analog
Terminal Surface Treatment:
Solder
Product Name:
Troduct Name.
Linear bipolar analog switch
Linear bipolar analog switch
Linear bipolar analog switch Voltage Rating And Type Per Characteristic:
Voltage Rating And Type Per Characteristic: 36.0 volts power source
Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature:
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document:
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity:
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit Shelf Life:
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit Shelf Life: N/a
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit Shelf Life: N/a
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit Shelf Life: N/a Unit Of Measure:
Linear bipolar analog switch Voltage Rating And Type Per Characteristic: 36.0 volts power source Nuclear Hardness Critical Feature: Hardened Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 40 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: