

View Online at <https://aerobasegroup.com/nsn/5962-01-393-6094>

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Pacer dawn

**Features Provided:**

Burn in and electrostatic sensitive and monolithic and ultraviolet erasable and programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

13 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, programmed-uv eprom, 64k (8k x8)

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Memory Device Type:**

Eprom

**Special Features:**

Electrostatic discharge sensitive; altered item, make from p/n 5962-8751501la

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0