

View Online at <https://aerobasegroup.com/nsn/5962-01-394-0347>

Body Length:

Between 1.260 inches and 1.280 inches

Body Width:

Between 0.290 inches and 0.310 inches

Body Height:

Between 0.180 inches and 0.200 inches

Maximum Power Dissipation Rating:

1.2 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Burn in, mil-std-883, class b and bipolar and electrostatic sensitive and hermetically sealed and monolithic and programmed and tested to mil-std-883

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

20 input

Criticality Code Justification:

Feat

Case Outline Source And Designator:

D-9 mil-m-38510

Current Rating Per Characteristic:

100.00 milliamperes reverse current, dc and 1.00 milliamperes reverse current, dc microamperes and 180.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, pal, valid remote terminal id comparator

Voltage Rating And Type Per Characteristic:

-1.5 volts input and 5.5 volts input and -0.5 volts power source and 12.0 volts power source

Time Rating Per Characteristic:

35.00 nanoseconds input to output access

Memory Device Type:

Pal

Special Features:

Esd; altered item programmed from 14933 8412906lx using pg639000-01 program

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0