

View Online at <https://aerobasegroup.com/nsn/5962-01-394-0347>

**Body Length:**

Between 1.260 inches and 1.280 inches

**Body Width:**

Between 0.290 inches and 0.310 inches

**Body Height:**

Between 0.180 inches and 0.200 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Pacer dawn

**Features Provided:**

Burn in, mil-std-883, class b and bipolar and electrostatic sensitive and hermetically sealed and monolithic and programmed and tested to mil-std-883

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

20 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes reverse current, dc and 1.00 milliamperes reverse current, dc microamperes and 180.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, pal, valid remote terminal id comparator

**Voltage Rating And Type Per Characteristic:**

-1.5 volts input and 5.5 volts input and -0.5 volts power source and 12.0 volts power source

**Time Rating Per Characteristic:**

35.00 nanoseconds input to output access

**Memory Device Type:**

Pal

**Special Features:**

Esd; altered item programmed from 14933 8412906lx using pg639000-01 program

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A458a0