

View Online at <https://aerobasegroup.com/nsn/5962-01-394-0350>

Maximum Power Dissipation Rating:

1.2 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Pacer dawn

Features Provided:

Electrostatic sensitive and bipolar and burn in, mil-std-883, class b and monolithic and programmed and tested to mil-std-883

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

20 input

Criticality Code Justification:

Feat

Current Rating Per Characteristic:

100.00 milliamperes reverse current, dc and 210.00 milliamperes reverse current, dc absolute and 1.00 milliamperes reverse current, dc microamperes

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, pal, memory and i/o address decode

Voltage Rating And Type Per Characteristic:

-1.5 volts input and 12.0 volts input and -0.5 volts power source and 12.0 volts power source

Time Rating Per Characteristic:

30.00 nanoseconds delay

Memory Device Type:

Pal

Special Features:

Esd; altered item from m38510/50501blx using program instructions pg6390000-01

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0