## NSN 5962-01-394-2173



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-394-2173 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.130 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and programmed and ultraviolet erasable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 16 input **Current Rating Per Characteristic:** 24.00 milliamperes output sink and 70.00 milliamperes supply **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital programmed **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source and -3.0 volts input and 7.0 volts input **Capitance Rating Per Characteristic:** 7.00 input picofarads and 7.00 output picofarads **Memory Device Type:** Pal **Special Features:** Programmed iaw drawing 111051 cage 35012 with sd980347-001 **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5962-01-394-2173

Memory Microcircuit - Page 2 of 2



## Demilitarization:

Yes - demil/mli

Fiig:

A458a0