NSN 5962-01-394-5250

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-394-5250

Body Length:
Between 0.375 inches and 0.395 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.140 inches and 0.160 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Used on m1a2 tank
Features Provided:
Hermetically sealed and burn in and uncompensated and wideband and w/resistor
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
45.0 volts power source
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: